



SOLVENTS / PENETRANTS – LOW ODOUR

Recosol 121

DESCRIPTION

Specialty hydrotreated, biodegradable paraffinic fluid designed for use in spark erosion machines, emulsion polymer formulations and lamp oil and rolling oil applications. **Recosol 121** has approval to be used in the manufacture of packaging for use in the food and pharmaceutical industries.

FEATURES

A clear, water white fluid with low volatility.

Highly refined product with a low odour and reactivity.

Burns cleanly and is ideal for low odour lamp formulations.

Can provide thin film lubrication and good penetration as a rolling oil.

Approval for use in the manufacture of food and pharmaceutical packaging.

Highly Refined – **Recosol 121** is chemically stable and non-regulated for storage and handling.

Safety – **Recosol 121** has a high flash point compared to flammable liquids and is a non-toxic product.

PACKAGING

Recosol 121 is available in IBCs (1000 litre bulk containers), drums and 20 litre containers.

SAFETY

Please consult the MSDS on **Recosol 121** before use. **Recosol 121** is most unlikely to pose any toxic hazard in normal operation.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Specific Gravity.....	0.815
Flash Point (open cup).....	119°C
Boiling Range	258–319°C
Kinematic Viscosity @ 40°C	2.5 cSt



MSDS available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033